

Texas Dairy Matters

Higher Education Supporting the Industry

PREPARE FOR SUMMER HEAT STRESS

Ellen R. Jordan, Ph.D.
Extension Dairy Specialist
Department of Animal Science
Texas A&M AgriLife Extension Service
The Texas A&M University System

Planning to minimize heat stress on your cows can be done at any time of the year. Although the temperature may be pleasant today, in Texas it's never long before we see the temperature rise.

Recent research from the University of Arizona on higher producing cows has indicated that whenever the temperature-humidity-index (THI) averages over 68 we should be providing cooling. The difference between a THI of 72 and 68 was nearly 5 pounds of milk per day.

Start by deciding whether you need to fine tune the cooling system you have or provide additional cooling. Herds with inadequate cooling may see milk production losses of 20 percent or more. If you already think you have plenty of cooling, now is the time for a spring check-up. Adjusting when cooling begins based on the new THI of 68.



If your herd doesn't have enough cooling, build shades as your first defense against summer heat stress. Provide 38-48 square feet of shade per cow. Use solid shade rather than slatted shade. Make the roof 11-14 feet high to minimize reflected solar radiation. Orient the shade north and south to allow the sun to dry the area under the shade.

Groom the area under the shade so cows have a dry place to lie down. If you already have shades, check to make sure they meet the guidelines described above. Repair shades that have been damaged.

Next, evaluate your holding pen cooling. Does a roof provide shade? If not, add shade. Install soakers and fans to cool cows while they wait to be milked. Mount fans at a 30 degree angle so air blows downward around the cow. Install parlor exit lane sprinklers to increase cooling beyond milking time.

Make sure all fans are working. Clean the fans to improve their energy efficiency as well as to enhance air movement. Repair water lines that may have ruptured during the winter. Replace spray nozzles in sprinkler systems where needed. Check the electrical system to ensure that fans and sensors will work properly when needed.

Add sprinklers at feed bunks to encourage cows to maintain dry matter intake. Put the sprinklers on a timer so cows are soaked to the skin and then allowed time to air dry.

With the drought, conserving water while cooling cows is a must. If not already in place, consider a system upgrade that adjusts the soak and cool times with the temperature. Work at Kansas State indicates you should increase soaking frequency at the feed lane as temperature increases. Soaking will require .35 gallon of water per headlock per soaking cycle. Adjust the soakers based on the following temperature ranges:

- a. less than 82° F once every 15 minutes
- b. 83 – 87 °F once every 10 minutes
- c. More than 87 °F once every 5 minutes

An ideal free stall barn has a roof pitch of 4 feet per 12 feet and an open ridge vent to encourage air flow. Side walls should be a minimum of 12 feet high with 14 feet preferable. Locate fans over the beds, above the feed bunk or both.

Although we usually discuss shade and cooling for the milking herd, cooling is just as important for dry cows and heifers. At a minimum, provide dry cows, heifers and calves with shade.

Check water supplies. Cows may double their water intake during the summer. If you've expanded your herd, verify that your water supply system can keep up with the increased water demand this summer. Provide baby calves with water as well. Milk isn't enough. Prepare now to combat heat stress so production losses are kept to a minimum this coming summer.

<http://texasdairymatters.org>

March, 2013

Educational programs of the Texas A&M AgriLife Extension Service are open to all people without regard to race, color, religion, sex, national origin, age, disability, genetic information or veteran status. The Texas A&M University System, U.S. Department of Agriculture, and the County Commissioners Courts of Texas Cooperating